


Overview



1. Auto Adjust
2. Menu/Select
3. OSD Navigation/Input Select

4. Power LED
5. Power

Models

PD974AA #ABA

Technical Specifications

Panel	Type	Active matrix, thin film transistor (TFT)	
	Viewable Image Area (diagonal)	19 in (48.25 cm) maximum viewable	
	Screen Opening (W x H)	14.9 x 12.0 in (38.0 x 30.5 cm)	
	Viewing Angle (typical)	176 degrees horizontal/176 degrees vertical (10:1 minimum contrast ratio)	
	Brightness (typical)	Up to 250 nits (cd/m ²)	
	Contrast Ratio (typical)	Up to 1000:1 (typical)	
	Response Rate (typical)	<16 ms (typical rise + fall)	
	Pixel Pitch	0.294 mm	
	Color Depth Support	16.7 million colors	
	Video/Other Inputs	Plug and Play	Yes (supports VESA DDC2B; PC2001 compliant)
		Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)
		Input Signal	Two connectors: one 15-pin mini D-sub analog VGA; and one DVI-I (VGA analog or digital)
		Input Impedance	75 ohms ± 2%
Sync Input		Separate sync (HSYNC/VSYNC); composite sync, Sync on Green (activated through on-screen display)	
Video Cable		VGA to VGA, DVI-D to DVI-D, and DVI-I to VGA	
Video Cable Length		78 in (2.0 m)	
Signal Interface/ Performance		Horizontal Frequency	30 to 82 kHz
		Vertical Frequency	56 to 75 Hz
		Native Resolution	1280 x 1024 @ 75 Hz analog 1280 x 1024 @ 60 Hz digital
	Maximum Resolution (Analog)	1280 x 1024 @ 75 Hz analog	
	Maximum Resolution (Digital)	1280 x 1024 @ 75 Hz digital	
	Preset VESA Graphic Modes (non-interlaced)	640 x 480 @ 60 Hz, 72 Hz, 75 Hz	
		720 x 400 @ 70 Hz	
		800 x 600 @ 60 Hz, 72 Hz, 75 Hz	
		1024 x 768 @ 60 Hz, 70 Hz, 75 Hz	
		1280 x 1024 @ 60 Hz, 75 Hz	
	Preset MAC Mode	832 x 624 @ 75 Hz	
		1152 x 870 @ 75 Hz	
	Preset VGA Mode	640 x 480 @ 60 Hz, 72 Hz	
	Preset SUN Mode	1152 x 900 @ 76 Hz	
	Fail Safe Mode	Yes (limits out of range signal messages)	
Maximum Pixel Clock Speed	140 MHz		
User Programmable Modes	Yes, 15		
Anti-Glare	Yes		
Anti-Static	Yes		
AssetControl	Yes (accessible on HP Compaq Business Desktops featuring Intelligent Manageability)		
Default Color Temperature	Yes (6500k, 9300k, SRGB, Custom User)		
On Screen Display (OSD) Controls	Buttons or Switches	Power on/off; 3-button OSD; second level OSD buttons include dual-input switch, dedicated auto adjust switch	
	Languages	English, Spanish, French, German, , Italian, Japanese, Simplified Chinese	

Technical Specifications

	User Controls	Size and Positioning Contrast Brightness Clock, Clock Phase Selectable Color Temperature Serial Number Mode Displayed Sleep Timer Input Selection Factory Reset Individual Color Contrast Full-screen Resolution
Power	Power Supply	Auto-ranging, 90 to 265 VAC; internal power supply
	Input Power	100 ~ 240 VAC
	Nominal Current	1.5 A maximum
	Frequency	50 ~ 60 Hz
	Average	33 watts when displaying standard office software
	Typical Power Consumption	< 40 watts
	Maximum	< 60 watts
	Power Saving	< 2 watts
	Off Mode	0 watts (when master power switch is in the off position)
	Power Cable Length	70 in (1.8 m); non-captive
Mechanical	Dimensions (H x W x D)	Unpacked with stand 16.8 (minimum) to 22.3 (maximum) x 15.9 x 8.3 in (42.7 (minimum) to 56.6 (maximum) x 40.4 x 21.1 cm) Base area (Footprint D x W) 8.3 x 12.2 in (21.1 x 30.9 cm) Panel only (without stand) (h x w x d) 13.2 x 15.9 x 3.1 in (33.5 x 40.4 x 7.9 cm)
	Weight	Unpacked with stand 16.5 lb (7.5 kg) Unpacked without stand 10.5 lb (4.75 kg) Packaged 23.5 lb (10.7 kg)
	Tilt Range	-5 degrees to +35 degrees
	Swivel Range	± 50 degrees horizontal swivel
	Height Adjustable	Yes (5.1 in/13 cm adjustment range)
	Pivot Rotation	Yes, 90 degrees
	Base	Ships detached and is removable after installation
Environmental	Temperature – Operating	41° to 95° F (5° to 35° C)
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)
	Humidity – Operating	20% to 80%
	Humidity – Non-operating	5% to 95%
	Altitude – Operating	0 to 13,000 ft (0 to 4,000 m)
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,192 m)
Options	Desktop Access Center	Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions. Sold separately; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.
	HP Flat Panel Speaker Bar	Powered directly by the monitor, seamlessly attaches to the monitor's bezel to bring full

Technical Specifications

Other	Accessories Included	multimedia support to select HP flat panel monitors. Features dual speakers with full sound range and external jack for headphones. Sold separately, part number PF804AA. For more information, refer to the HP Flat Panel Speaker Bar QuickSpecs.
	Software	VGA to VGA cable, DVI-D to DVI-D cable, DVI-I to VGA cable, USB cable, user CD-ROM with Pivot Pro software
	Software	Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.
	Software	HP Display LiteSaver feature lets you schedule Sleep mode at preset times to help protect the display against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	User Guide Languages	English
	Warranty Languages	English
	Color	Carbonite
	VESA Mounting	Yes (swing arm/wall mount not included); base must be removed for mounting options)
	VESA External Mounting	Yes (standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
Certification and Compliance		Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification
Compatibility		VESA Video Signal Standard (VSI) Compliant video cards have been tested and proven compatible for use with the HP L1955 Flat Panel Monitor. Recommended for use with HP products.
Service and Warranty		Three years parts, labor, and on-site service. 24-hour 365-day 1-800 technical support. Replacement options include 2nd business day on-site service or next business day direct replacement. With direct replacement, HP will ship a replacement display product directly to you. Using the shipping labels provided, return your failed display to HP. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

© 2004 Hewlett-Packard Development Company, L.P.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries.

All specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. All performance specifications are provided by the component manufacturer. Performance specifications represent component manufacturer averages and actual performance may vary.